- on USDW's which may be affected by the injection operation. It is EPA policy to expect that any Underground Source of Drinking Water (USDW) overlying an injection zone has the potential for being contaminated by that injection. Therefore, the data submitted as Attachment E is inadequate for our review procedures. There are other USDW's overlying injection zones besides the Judith River (e.g., Fox Hills, Hell Creek, and the Fort Union, all of which meet the definition of a USDW). Please elaborate on your submittals for each permit, giving us the geologic name and depth to the bottom of all USDW's occuring above the injection zones.
- 6. GEOLOGICAL DATA ON INJECTION AND CONFINING ZONES: With reference to Attachment G, the geologic data submitted must be expanded upon. Please submit, in narrative form, the appropriate geologic data on the injection zone and confining zones including: lithologic description; geological name; thickness; depth and fracture pressure (and how the fracture gradient was determined). If possible, a local geological map would be very helpful.
- 7. OPERATING DATA: Attachment H requires that the maximum daily injection rate and pressure be submitted. You have stated the average rate and pressure, but not the maximum. Please do so for each well.

WELL-SPECIFIC DEFICIENCIES

In addition to addressing the issues mentioned above for each well.

please respond the the well-specific issues listed below:

VICKERS #1

- 1. You have submitted well data for all wells within a one-mile radius of the subject well as Attachment C. One of the those wells is the Tribal #1. The data submitted was unclear. Who owns/operates the Tribal #1? Is it an active producer at this time? If not, what is its status?
- 2. In Attachment H (Operating Data), you state that water analyses for the two injection source wells are attached. One of the source wells referenced is the Mason #7-16, but no analysis is included for that well. Please submit this analysis or explain why it was not included.

GOINGS #1

- i. Since you have stated that the Goings #1 is located on Indian Lands, please indicate whether or not there is a current Bureau of Land Management permit for this well.
- 2. With regard to your submittal for Attachment A, the top portion of the topographic map in Exhibit I is missing. This missing portion is within the one-mile radius of the subject well. Please submit a new topographic map with the missing portion added.

CLARK #1

1. Because the Clark #1 had not commenced injection prior to September 2, 1983 (which is the date of publication for the proposed UIC regulations, and the cut-off date for "grandfathering in" aquifer exemptions for existing wells), you will need an aquifer exemption prior to receiving a permit. Aquifers with less than 10,000 mg/l total dissolved solids qualify as USDW's and must receive an exemption before EPA can issue a permit to inject (see 40 CFR Parts 144.7 and 146.4). Minumum public comment period for aquifer exemptions is 30 days. The Goings #1 and the Vickers #1, which commenced injection on 3/22/82 and 4/1/83, respectively, were granted automatic aquifer exemptions upon UIC program approval. In order to proceed with the aquifer exemption, we will need a brief description of the nearest USDW including location, water quality and water use. The aquifer exemption issue must be resolved before any permitting action can proceed.

As soon as we receive all the information listed above, we will be able proceed with processing the permits and the aquifer exemption. Please should the required information to the Denver Regional office as soon as saible, but no later than September 6th. If you have any questions garding this letter, or on the status of your application, please contact are Clemmens or Michael Liuzzi at (303) 844-2731.

3

Mr. Jake Eisel Century Oil and Gas Corporation 7887 East Belleview, Suite 800 Englewood, Colorado 80111

Dear Mr. Eisel:

You are hereby requested to submit permit applications for the following wells by July 30, 1984:

Field

Well Name

NW Poplar

Goings No. 1 Vickers No. 6-15 Clark No. 1 Cox No. 1

EPA is requiring permit applications for these wells for the following reasons: 1)The agency has determined that salt water disposal (SWD) wells pose a significant threat to Underground Sources of Drinking Water (USDW's) in this area and is therefore permitting them as soon as possible and; 2)EPA has received assertions from the Bureau of Indian Affairs (BIA) of ground water contamination as a possible result of salt water disposal activities on the Fort Peck Indian Reservation. Since the East Poplar and Northwest Poplar fields are the area of greatest concern to the tribe and the BIA, we are requesting that permit applications for wells from these fields be submitted first.

Please complete one of the enclosed application forms for each well listed by July 30, 1984. Be sure that all the applications are complete and that all required attachments are included. Submit the completed applications to:

Chief, Drinking Water Branch U.S. Environmental Protection Agency (8WM-DW) 1860 Lincoln Street Denver, Colorado 80210 The SWD wells led above may continue to operatunder current authorization by rule until:

The effective date of a permit (activities will then be authorized by permit);

The denial of a permit (the well will no longer be authorized to inject); or

The owner or operator fails to submit the permit application within the time period specified in this notice (at which time the authorization to inject will be revoked).

I encourage you to contact either Richard Long in the EPA Denver Regional Office (Phone: (303) 844-3914) or William Engle in the EPA Montana Operations Office (Phone: (406) 449-5414) as soon as possible if you have any questions.

Sincerely yours,

John F. Wardell, Director, Montana Operations Office

Enclosures: Permit Application Forms

به کارمین آنا

Permit Application & Attachments (P&A Approval Request)


Correspondence to EPA


029N 050E


ROOSEVELT Swdw Located: SWSE PRCK NR, NW, ROOSEVEL

MT2002-0002

Sidney 2/11/83 The Western Compa Date 2/11/83 Western District Operator Century Oil & Gas Date___ F. Receipt 661581 Vicker Lease____ ____Well No.___ of North America Sec. 6-29N-50E Wildcat __Location____ Field_ County_ Roosevelt TREATMENT REPORT Montana State.___ Baker "R" Size Tubing 2 3/8 Tubing Perf. 3803 Type Packer Baker "R" Set At 3, Wt. 15.5 Set From 0 To 4,175 Size Liner — Wt. ____Set At___3,803 Liner Set From ____ To ____ Open Hole: Size ___ From ____ To 1 Intervals 3,960-4,060 ____Holes Per Foot_ Casing Perforations: Size____ N/A Previous Treatment N/A _Prior Production___ FLUID PUMPED AND Pad Used: Yes \(\subseteq \text{No } \subseteq \text{Yed Type} \) TREATMENT DATA: CAPACITIES IN BBLS. Treating Fluid Type: Oil Water Acid Misc. Foam Emulsion Fluid Description Fresh Water W/gal. Packer 14.7 Tubing Cap.___ Treating Fluid Volume Gals.___ Fluid Casing Cap.__ 69.6 Annular Cap. Total Prop Quantity______Lbs. Prop Type: Sand _ Beads _ Special _ None _K Open Hole Cap ._ Prop Mesh Sizes, Types and Quantities _____ Fluid to Load ___ Hole Loaded With Formation Water Treat Via: Tubing A Casing Anul X Tubing & Anul. Pad Volume ____ Treating Fluid_ 73.5 Flush Tubing 42 Auxiliary Materials____ Overflush _____ Total to Recover_ Circulate 73.5 bbls Fresh Water with 5 gal. Packer Fluid 42 Down Annulus. Establish Injection Rate Down Tubing. Time Treating Pressure-Psi Barrels Fluid Ini. Rate Tubing Casing AM/RIM Pumped BPM REMARKS— Test Lines; Safety Meeting 10:32 4.5 () 0 0 Start Water Down Annulus 10:34 350 8 0 Annulus Full: Start Circulation to Pit 11:10 500 70 Shut Down 11:18 0 300 1.6 Resume Down Annulus 70 11:20 300 73.5 1.6 Shut Down 12:25 0 Start Injection Test 12:27 1.0 Increase Rate; Pressure Break 600 psi 1100 () 12:30 1.8 Increase Rate 1000 0 4 12:37 1500 0 22 3.2 Increase Rate 12:40 800 0 26 1.0 Decrease Rate Increase Rate 0 5.0 1950 5.0 Shut Down 1.00 42 0 Treating Pressure: Min. 800 Max. Inj. Rate on Treating Fluid 2 1200 Gene Mullholand Customer Representative ____ ___Avg.___ Western Representative Ed Schleinger __Rate on Flush____ Distribution 1 copy: 717 17th St. Suite 1770 750 Flush Dens. lb/gal 8.33 Avg. Inj. Rate _____2 Denver, CO 80200 Final Shut-in Pressure ____ ___in ____ Minutes. Operator's Maximum Pressure _ 1 copy: Sidney District Job Number 697212 IBDP = 750 | PRESSURE X 1000 PSI Shut IBOWT 7 6 5 4 14 | 12 | 1 8 18 D-10 BPM Scale Increase Rate. 29_BBLS____ 12:50







COMPRESSIVE STRENGTH (p.s.). Curing Temp.]	ng mud wt.	mud type	a loss	f slurry	der	tive by %	eive	of cement	of cement	NG		String	String	ce String	No.	Hole Size	og Interval	Log Interval	1-Logger	1-Driller	Vo.		ng Measured from	Reasured from	anent Datum_					9)						LING NO.			
COMPRESSIVE STRENGTH (p.s.i. Curing Temp.) Compressive Strengt	10万年 村田川			のできるできる。		情報を				Surface		5.5"			1	7-7/8"	3000	15,00	6),511	6500	ONE	7-21-81			G.			,			LOCATION	COUNTY		FIELD	WELL_	COMPANY				
PRIMARY CEMENTING PROCEDURE Protective Production Programment Processor Proces		45.00					大き			P	P	131	* S										в.	ļ 1.			TWP					AGCOPA		WILDCA	VICKER	Catal a Cat	CENTUR			
COMPRESSIVE STRENGTH (p.s.i. Curing Temp.) Time Elapsed Surface Protective Production Li 48 hrs. FF FF FF FF FF FF FF FF FF	100					S. Sandaria			300	rotection	RIMARY CE			+	9	Witnessed (Recorded F	Equip	Est. Cemer	Max. Rec.	Dens.	Type Fluid		1_Ft.Above	Ele		29N					RLT		F	NO. 6-	5	% IIO			
COMPRESSIVE STRENGTH (p.s.i. Curing Temp.) Time Elapsed Surface Protective Production Li 48 hrs. FF FF FF FF FF FF FF FF FF	t									Produ	MENTING	1			pe Joint	34	3v	Location	t Top	Temp.	Visc.	in Hole		Permanent D	v. 2546'-		Ш	l.				316	3		5	- 1				
COMPRESSIVE STRENGTH (p.s.i. Curing Temp.)	-									ction	ATA	SURFACE				MR. MULH	WINDEN	6030-721	31101				GL_	III NA	1000		L			-	_	T.					RATION			
COMPRESSIVE STRENGTH (p.s.i. Curing Temp.)										Liner		TD			Bottom	OLLAND	- L	_					2546"	2556	255/	Elevations:				LPUL OWNER	Other Services									
24 hrs.	-					_									_	(col	MP	RE	SS	IVI	E S			_		p.s.i	. Cu	ring	Ten	np.)					*******				
Hour - Date	48	hr hr	s. s.	psed									Su	urfac	ce			۰F			_		Pro	ote	ctiv	e		°F	+			Prod	duc	tion	۰F	=				
Priceding fluid Partial None Pipe reciprocated during Pumping: Yes No Pipe reciprocated after plug down: Yes min., No Pipe reciprocated after plug down: Yes min., No Pipe reciprocated after plug down: Yes min., No	Plug	on ease	bo	ttom	•	. 10	nt	IM	AR	Y (CEM	-			10		DU	-11	HOI ST OP	ER	AT	ROI OF ION	M	RU		BI	AS:	MAX RID(SPE (. GE N	ED IO.		R		•	; TOO	E ACIN	TYPE	CO		
Tool Model No. COMB	Prec	edir	ng f	fluid		11/2	24			Par	rtial .		\	Volu		_	,_					_ b	bls.	37	1300															_
Source Type Strength Source Serial No. NEUTRON Serial S	Too Dias	Meter meter ecto	ode	l No	-).		nth.	3	OM . 2	B.			611											To To	ol S ol I	Seria Mode eter	No.		; Spa	cing		-							
Run DEPTHS Speed T.C. Bkg. Cal. Sens. Zero Div. L or R Units Per Log Div. Sec. Cps. Settings Div. L or R Cps. Settings Div. L or R Cps. Sec. Cps. Cps. Settings Div. L or R Cps. Sec. Cps. Cps. Settings Div. L or R Cps.		_	e to	N. 5	Sou		-	2	2		MI			0							-				So	urc	е Ту	pe					_							
	No.	3	50 00	0 1	_	F F 6 L	151	1	Ft	45	lin.		+-	50	5.		1	91. 98.		Set Set	ting	38	Div.	0			Lo	its Pe g Div 10	r						al.	S	ens.			
					garan. P	ar 60		1700 00		COR.	1000	e de la companya de																					2	00	5	5	SPE (C T F	R U	M
200 S SPECTRUM		-	_	0	_			-		NAME OF	I		-		\dashv					0	0		A	MF	L	I	TU	DE	- 14	1 ∨	8	30								
200 S SPECTRUM 500 CCL -500 O AMPLITUDE-MV 80 0 GR API 200			-					2	\						1	0	3 (00	0								-				}				MINISTERNAL STATES		- Company			